











# HDMI Extender

	Model	Product	Transmission Distantance	Power	HD BaseT	HDMI Input/Output	RS-232	IR Control	Size	Weight
1.	EX30-KVM (TX) EX30-KVM (RX)		1080P -30m MAX(Cat6/Cat6e)	Without Power	/	165MHz/165Gbps single channel 1080P@60Hz With USB port For KVM Function	/	/	L61mm W43mm H22mm	150g (Pair)
2.	EX60-3D-IR		1080p 8-bit 60m( Max. )	Dual	/	Input Video Signal: 0.5-1.0 Volts P-P Input DDC Signal: 5 Volts P-P ( TTL ) Video Format: DTV/HDTV: 480i/576i/480p/576p/720p/1080i/1080p 3D Video Video Output: HDMI	/	/	L84mm W60mm H22mm	206g (Pair)
3.	EX-60-C		1080P -60m MAX(Cat6)	Dual	/	Input Video signal: 0.5~1.5Volts p-p Output DDC signal: 5Volts p-p (TTL) Audio format: DTS-HD/Dolby-true HD/LPCM7.1/DTS/Dolby-AC3/DSD Video input/output : 1080p/1080i/720p/576p/480p/480i@24/50/60Hz	/	/	L82mm W57mm H27mm	450g (Pair)
4.	EX-HD60S		1080P -60m MAX(Cat6)	Dual PoC	/	Input Video signal: 0.5~1.5Volts p-p Output DDC signal: 5Volts p-p (TTL) Audio format: DTS-HD/Dolby-true HD/LPCM7.1/DTS/Dolby-AC3/DSD Video input/output : 1080p/1080i/720p/576p/480p/480i@24/50/60Hz	/	38KHz (可選)	L82mm W46mm H23mm	380g (Pair)
5.	EX60P-PoC (TX) EX60P-PoC (RX)		1080P -60m MAX(Cat6/Cat6e)	PoC	/	Maximum data rate: 6.75Gbps Maximum pixel clock: 165MHz Audio format: DTS-HD/Dolby-true HD/LPCM7.1/DTS/Dolby-AC3/DSD Video input/output : 1080p/1080i/720p/576p/576i/480p/480i @24/50/60Hz	/	38KHz	L82mm W46mm H23mm L86mm W86mm H38mm	450g (Pair)



# HDMI Extender

	Model	Product	Transmission Distantance	Power	HD BaseT	HDMI Input/Output	RS-232	IR Control	Size	Weight
6.	EX60-KVM (TX) EX60-KVM (RX)		1080P -60m MAX(Cat6/Cat6e)	Dual	/	Input Video signal: 0.5~1.5Volts p-p Output DDC signal: 5Volts p-p (TTL) Audio format: DTS-HD/Dolby-true HD/LPCM7.1/DTS/Dolby-AC3/DSD video input/output : 1080p/1080i/720p/576p/480p/480i@24/50/60Hz	/	38KHz	L61mm W43mm H22mm	250g (Pair)
7.	M-HK100B (TX) M-HK100B (RX)		4K@30Hz-120m MAX(Cat6)	PoC	/	Input Video signal: 0.5~1.5Volts p-p Output DDC signal: 5Volts p-p (TTL) Max bandwidth: 340MHz, digital Max baud rate: 3x3.4Gbps	/	30-60KHz	L94mm W72mm H25mm L86mm W86mm H38mm	700g (Pair)
8.	M-HW200 (TX) M-HW200 (RX)		1080P -200m MAX	Dual	/	Compression format: H.264 Maximum data rate: 6.75Gbps Impedance: 100Ω Transmission delay: 0.8 seconds Wireless standard: 802.11a, 802.11n, 802.11ac Frequency: 5150~5250MHz, 5475~5850MHz 640x480 60Hz/800x600 60Hz/1024x768 60Hz/1280x720 60Hz/1280x960 60Hz/1280x1024 60Hz/1920x1080 60Hz/1920x1080i 60Hz	/	/	L116mm W68mm H20mm	TX: 700g (Pair) RX: 350g (Pair)